

GasAlert Max XT II



Simple operation with pump

The rugged GasAlertMax XT II reliably monitors for up to four gas hazards and combines straightforward one-button field operation with an integrated sampling pump. Tamper-proof, user-adjustable options enable the instrument to be customised to suit your application. Confined space entry and remote sampling have never been so easy with new, intelligent SmartSample pump technology. Minimise pump blockages and improve remote sampling result accuracy. Powered by a rechargeable battery pack that provides runtime for an entire 13 hour shift, the compact GasAlertMax XT II comes with standard event logging and datalogging. The GasAlertMax XT II is fully compatible with the MicroDock II automated test and calibration system.

H₂S

CO

O₂

LEL

Standard Package Contents

- Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing
- Rechargeable lithium polymer battery
- Charging adaptor
- 3 ft. / 1 m calibration hose with quick connect
- 10 ft. / 3 m sampling hose with particulate filter and quick connect
- Reversible screwdriver
- Kit of five spare pump filters
- Manual
- Multi-language CD manual

General Specifications

| | |
|------------------------------|---|
| Size | 5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm |
| Weight | 11.1 oz. / 316 g |
| Typical battery life | 13 hours @ 32°F / 0°C 10 hours @ -4°F / -20°C Recharges in 6 hours |
| Certifications and approvals | <p>Class I, Div. 1, Gr. A, B, C, D</p> <p>American Bureau of Shipping</p> <p>ATEX: X g II 1 G</p> <p>Ga Ex ia IIC T4</p> <p>IECEX: Ga Ex ia IIC T4</p> <p>CE: European Conformity</p> |
| Warranty | Full two year warranty including all sensors |

