

# SMART 3 BLIZZARD

## Refrigerant Gas Detector

Precision without compromise: the Sensitron SMART 3 Blizzard provides infrared refrigerant gas detection with wireless interface – ready for the future.



SMART 3 Blizzard has been designed to monitor refrigerant gases with maximum precision and minimal intrusion. It enables safe, remote maintenance without the need for physical access to the device. Whether used in HVAC-R applications or non-classified areas, SMART 3 Blizzard combines reliability, intelligence and user-centric design for enhanced safety and operational efficiency.

## FEATURES

### Ideal for machine rooms & light industry

- Detects refrigerant gases in safe (unclassified) areas
- Multicolour LED ring and internal buzzer provide clear alarms, so you can act quickly to secure your site
- Simple sensor replacement
- Continuous self-diagnostics
- Infrared sensor

### SENSE

- Wireless interface available on PC and mobile devices
- Set alarm thresholds
- Check detector status
- Update firmware
- Download reports

### Fully compliant

- SMART 3 BLIZZARD is fully compliant with the following standards and regulations:
- EN 378-3
- EN 14624
- EN 50676
- IEC 60335-2-40 Annex LL
- ANSI/ASHRAE 15
- CSA B52: 2023
- F-Gas Regulation EU 573/2024
- SIL2 certified according to EN50402

## GASES & RANGES

GASES & RANGES		
GAS	SENSOR	RANGE
R454B	Infrared	0-100% LFL
R32	Infrared	0-100% LFL
R1234YF	Infrared	0-5000ppm
R1234ZE	Infrared	0-5000ppm
R134A	Infrared	0-5000ppm
R404A	Infrared	0-5000ppm
R410A	Infrared	0-10000ppm

# SPECIFICATIONS

DEVICE SPECIFICATIONS	
<b>SIZE</b>	130 x 130 x 52 mm
<b>WEIGHT</b>	450g
<b>ENCLOSURE MATERIAL</b>	Polycarbonate
<b>INGRESS PROTECTION</b>	IP454
<b>CABLE GLAND ENTRIES</b>	2 x M20 Optional 6x M16
<b>OPERATING VOLTAGE</b>	12-24 Vdc
<b>POWER</b>	73 mA at 24V DC
<b>OUTPUT</b>	2 relays 4-20 mA Analog Sounder: 63dB at 1 meter
<b>INDICATORS</b>	Light: 4 Smart LED -10°C to +50°C
<b>OPERATING TEMPERATURE</b>	0 / 95% RH non condensing
<b>HUMIDITY</b>	EN 61000-6-3:2007 + A1:201; EN 50270:2015
<b>EMC COMPLIANCE</b>	
<b>REFRIGERATION STANDARDS COMPLIANCE</b>	EN 378-3; EN 14624; EN 50676; IEC 60335-2-40 Annex LL; ANSI/ASHRAE 15; CSA B52: 2023; F-Gas Regulation; EU 573/2024
<b>WARRANTY</b>	2 years on electronics 1 year on sensor



## Australian Distributor

**K. D. Fisher & Co. Pty** Ltd ABN 27 007 879 647

Head office 18 Benjamin Street St Marys SA

5042 **T** +61 8 8277 3288 **T** 1300 533 474

**E** [kdf@kdfisher.com.au](mailto:kdf@kdfisher.com.au) [kdfisher.com.au](http://kdfisher.com.au)

**Disclaimer** Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This document is not intended to form the basis of a contract.

### For more information:

t: +44 (0)1235 557700

e: [info@crowcon.com](mailto:info@crowcon.com)

w: [www.crowcon.com](http://www.crowcon.com)

Locate your Regional Sales Representative at:

[www.crowcon.com/contact-us/where-to-buy](http://www.crowcon.com/contact-us/where-to-buy)

© 2025 Crowcon Detection Instruments Ltd.

