



- ▶ **Tough reinforced plastic construction**
- ▶ **Light, easy operation**
- ▶ **Stock model for fast delivery**
- ▶ **Temperature range -10°C... +40°C**



Specifications	
Standards/approvals	N/A
Connection method	See table below
Air connection	Compete with 2 m tube (black) with 3mm i/D 6210-001 with 3 m tube
Alternative air connection	3mm I/D & 6mm O/D, which are available in different length
Electrical rating	N / A
Pressure range	Works with 6871, 6872, 6773, 6753, 6891, 6893, 6861, 6862, 6863, 6864, 6869 - dependent on tube length
Electrical rating	N/A
Contact configuration	N/A
Operating temperature range	-10° C to +40° C
Body material	Thermoplastic
Weight	0.2 kg

Recommended depression time is 30 seconds, for applications requiring a greater period please contact sales to discuss further.



## Dimensions

6210-0B



## Accessories

Part-Number	Description
6202-0001	Single - black, RAL 9005 guard
6202-0002	Single - grey, RAL 7035 guard
6202-0003	Twin - grey, RAL 7035 guard

## Order information

Stock models:  
 6210-0B with 2m tubing  
 6210-0001 with 3m tubing



### Australian Distributor

**K. D. Fisher & Co. Pty** Ltd ABN 27 007 879 647  
 Head office 18 Benjamin Street St Marys SA  
 5042 T +61 8 8277 3288 T 1300 533 474  
 E [kdf@kdfisher.com.au](mailto:kdf@kdfisher.com.au) [kdfisher.com.au](http://kdfisher.com.au)

**If you require a customized solution for your program contact our sales team.**