



- ▶ **Aluminium construction for harsh environments**
- ▶ **With strong conduit tubing**
- ▶ **Temperature range: -10°C to +40°C**

Specifications	
Standards/approvals	N/A
Air connection	Compete with 2 m tube (black) with 3mm I/D
Alternative air connection	3mm I/D & 6mm O/D, which are available in different length
Electrical rating	N/A
Pressure range	Works with 6871, 6872, 6773, 6753, 6891, 6893, 6861, 6862, 6863, 6864, 6869 - dependent on tube length
Electrical rating	N/A
Contact configuration	N/A
Operating temperature range	-10° C to +40° C
Body material	die-cast aluminium, powder coat black

Recommended depression time is 30 seconds, for applications requiring a greater period please contact sales to discuss further.



Dimensions



Accessories

Part Number	Description
6202-0001	Single Black RAL 9005 guard
6202-0002	Single Grey RAL 7035 guard
6202-0003	Twin Grey RAL 7035 guard



Australian Distributor

K. D. Fisher & Co. Pty Ltd ABN 27 007 879 647
 Head office 18 Benjamin Street St Marys SA
 5042 T +61 8 8277 3288 T 1300 533 474
 E kdf@kdfisher.com.au kdfisher.com.au

If you require a customized solution for your program contact our sales team.